



# Deployable Air Conditioning System

---

## Use

This cooling unit is built for the deployable EDAK 8 RU Equipment Case fitted with computing, networking or electronics equipment. The unit is robust and has been tested to Military Specification. It comes with a 1 year warrantee from the date of supply. The unit will dissipate heat from the case to a total capacity of 500 watts at 35 degree's Celsius Ambient temperature. The unit is not designed to operate above 50 degrees Celsius but is capable of operating to approximately 55 degrees Celsius for limited periods.



## Fitting

This unit is delivered ready for installation. The unit replaces the standard EDAK equipment case lid and is mounted onto the EDAK 8 Rack Unit case using the hinges provided on the side of the case.

## Features

### Gas

The Cooling unit consists of the compressor, the evaporator, the condenser and a capillary tube. These are interconnected by suitable copper pipes and filled with R417A environmental friendly green gas. A filter dryer is integrated into the cooling circuit. This provides protection against most foreign bodies that could contaminate the gas.

### Safety Devices

The cooling unit includes 2 safety devices. The high pressure monitor is set to turn the compressor off when the maximum operating pressure of 400 PSI is reached. It protects the system from excessive ambient temperatures above 65 degrees Celsius. The second safety device is a temperature cut out switch. This switch will turn the compressor off if the compressor malfunctions or the ambient temperature rises to approximately 55 degrees Celsius.

### Maintenance

The unit is maintenance free hermetically sealed system. The cooling unit has been filled in the factory with the required amount of coolant and tested for leaks. It has also been tested for electrical operation. The installed maintenance free fans use ball bearings with a life expectancy of approx 30,000 hours if used below 40 degrees Celsius.